




## HUSQVARNA 525RJD

A highly efficient, robustly built and versatile Husqvarna brush cutter. Comes with a combi guard, trimmer head and grass blade, which allow you to handle a range of demanding work tasks. Accepts attachment tools such as edger, hedge trimmer, pole saw, cultivator & sweeper for versatility. The patented X-Torq® engine gives you more power, less fuel consumption and less exhaust emissions compared to a conventional engine.



### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



### J-handle

Equipped with J-handle for greater versatility.

### Intuitive controls

The choke and purge are easy to reach and understand.



### X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



## FEATURES

- Intuitive controls
- J-handle for increased versatility
- Auto return stop switch for easy starting
- X-Torq® engine cuts emission and fuel consumption
- Air purge for easier cold starting
- Comfortable handles
- Detachable shaft easy transport and storage
- LowVib® sparing the user's arms and hands
- Skid plate for engine protection
- Easy to service and maintain starter
- Efficient air filter
- Adjustable harness hook eyelet

Technical Specifications	
<b>CAPACITY</b>	
Clutch engagement speed ( $\pm 120$ )	4000 rpm
Clutch engagement upper limit	4200 rpm
Idling speed	3000 rpm
Idling upper limit	3400 rpm
Maximum power speed	8500 rpm
Maximum rpm output shaft	6500 rpm
Power output	1 kW
Racing speed lower limit	10200 rpm
Torque, max.	1.2 Nm
Torque, max. at rpm	6000 rpm
<b>DIMENSIONS</b>	
Article gross weight	10000 g
Article net weight	9000 g
Cutting width	46 cm
Racing speed lower limit	10200 rpm
Tube diameter	24 mm
Tube length	1483 mm
Weight (excl. cutting equipment)	4.9 kg
<b>ENGINE</b>	
Cylinder bore	34 mm
Cylinder displacement	25.4 cm <sup>3</sup>
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Gear ratio	13
Ignition module air gap	0.3 mm
Spark plug	NGK BPMR8Y
<b>EQUIPMENT</b>	
Drive gear angle	30 °
Grass blade	Grass 255–4
Harness	Single harness
Saw blade	--
Trimmer head	T35 M10
<b>LUBRICANTS</b>	
Fuel consumption	600 g/kWh
Fuel tank volume	0.51 l
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	445 mm
Packaging length	1840 mm
Packaging volume	249.73 dm <sup>3</sup>
Packaging width	305 mm
Quantity in Master pack	1
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	114 dB(A)
Sound pressure level at operators ear	98 dB(A)
<b>VIBRATIONS</b>	
Daily Vibration (Aeqv)	3.3 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	2.3 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	4 h
Equivalent vibration level (ahv, eq) front handle	4.5 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	3.9 m/s <sup>2</sup>

