



# HUSQVARNA Z242F

Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore.



### Cast Iron Spindle Housings

Bold cast iron blade housings built for durability and featuring sealed ball bearings.



### Deluxe High Back Seat

The thick padded seat and soft outer cover offers superior support and comfort, while the open back gives added ventilation.

### ClearCut™ fabricated cutting deck

ClearCut™ deck technology features deep deck design, air flow control baffles, high performance blades and top discharge for superior cutting performance whether discharging, bagging or mulching.



### Automatic park brake system

The new patent pending park brake system automatically activates or deactivates as the steering levers are moved outward or inward, freeing the user of the task.



## FEATURES

- ClearCut™ fabricated cutting deck
- Deluxe High Back Seat
- Durable, cast iron spindle housings
- Automatic park brake system
- Convenient deck lift
- Ergonomic control panel
- Anti-slip foot area
- Bumper with integrated LED headlights
- Dust protection
- Rugged frame and casters ensure durability
- Rear engine guard
- Powerful two-cylinder Kawasaki engine
- No turning radius by individual wheel-drive

Technical Specifications	
<b>BATTERY</b>	
Battery capacity	18 Ah
Battery manufacturer	East Penn
Battery pack weight	7.03 kg
Battery type	Lead-Acid
Battery voltage	12 V
Cells per battery	6
Quantity of batteries/battery pack	1 pcs
Weight of one battery	15.5 lbs
<b>CAPACITY</b>	
Blade-tip speed	93.98 m/s
Net power at preset rpm	3600 rpm
Power output	21.5 hp
<b>CERTIFICATIONS</b>	
Clutch rating	117.96 Nm
Power rating	16033 W
<b>DIMENSIONS</b>	
Article gross weight	333390 g
Article net weight	263991 g
Base machine, height	101.6 cm
Base machine, length	190.5 cm
Base machine, width (chute down)	129.54 cm
Base machine, width (chute up)	110 cm
Base machine, width	122 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Deck thickness	3.4 mm
Seat back height	High
Weight	256.73 kg
Wheel size, Front	279 mm
Wheel size, Rear	457 mm
<b>ENGINE</b>	
Cylinder displacement	726 cm <sup>3</sup>
Cylinders	2
Engine cooling	Air
Engine name	FR Series
Motor/engine manufacturer	Kawasaki
Motor/engine model	651V
Fuel tank volume	13.25 l
Fuel tank volume	3.5 gal (US)
<b>EQUIPMENT</b>	
12V outlet	No
Air filter type	Auto-type Paper
All-Wheel Drive (AWD)	No
Anti-scalp wheels	1
Ball bearing wheels	No
Ball bearing front wheels	Yes
BioClip® kit	Available as accessory
Blade brake clutch (BBC)	Yes
Blade engagement	Electric clutch
Blade type	High-Lift blade
Blades	2 pcs
Collector	Available as accessory
Collector type	Fabric
Cup holder	Yes
Cutting deck type	ClearCut™ - Fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	Included
Detachable transmission	No
Drive method	Lever-operated

**Technical Specifications**

Drive system	Rear wheel drive
Drive wheels	Rear
Electric start	Yes
Fan-cooled pumps	Yes
Foldable seat	No
Headlights	Yes
Hinged armrests	Standard
Hour meter type	Digital with pre-programmed service intervals
Hydraulic equipment lift	No
Nose roller	Yes
Parking brake, type	Mechanical
Seat manufacturer	Seat King
Seat spring	Yes
Seat suspension	No
Seat type	Comfort high back
Throttle control	Yes

**LUBRICANTS**

Engine lubrication type	Full pressure with oil filter
Fuel consumption	4.012 l
Fuel tank location	Side (Single)
Fuel type, min	87 octane
Oil capacity	2.1 l
Oil cooler	No
Oil filter	Yes
Oil type	10W30
Power/fuel type	Gasoline

**MATERIALS**

Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	1084 g
PE total	715 g
PET total	0 g
Plastic foil	520 g
Plastic rigid	200 g
Plastic total	720 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS total	0 g
Rims, material	Steel
Seat material	Vinyl
Spindle/mandrel type	Cast iron

**PACKAGING**

Packaging height	876 mm
Packaging length	1981 mm
Packaging volume	2710 dm <sup>3</sup>
Packaging width	1562 mm
Quantity in Master pack	1

**SOUND AND NOISE**

Sound power level, guaranteed (LWA)	110 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	80 dB(A)