



HUSQVARNA Z248F

Performance and style hit the grass running with the all new Z200 series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore.



Automatic park brake system

The new patent pending park brake system automatically activates or deactivates as the steering levers are moved outward or inward, freeing the user of the task.



Cast Iron Spindle Housings

Bold cast iron blade housings built for durability and featuring sealed ball bearings.

ClearCut™ fabricated cutting deck

ClearCut™ deck technology features deep deck design, air flow control baffles, high performance blades and top discharge for superior cutting performance whether discharging, bagging or mulching.



Convenient deck lift

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.



FEATURES

- ClearCut™ fabricated cutting deck
 - Durable, cast iron spindle housings
 - Automatic park brake system
 - Convenient deck lift
 - Maintenance-free hydraulic transmission
 - Ergonomic control panel
 - Removable foot plate
- Anti-slip foot area
 - Bumper
 - Dust protection
 - Rugged frame and casters ensure durability
 - Rear engine guard
 - Kawasaki engines offer smooth, reliable power
 - No turning radius by individual wheel-drive

Technical Specifications	
BATTERY	
Battery capacity	18 Ah
Battery manufacturer	East Penn
Battery pack weight	7.03 kg
Battery type	Lead-Acid
Battery voltage	12 V
Cells per battery	6
Quantity of batteries/battery pack	1 pcs
Weight of one battery	15.5 lbs
CAPACITY	
Blade-tip speed	93.98 m/s
Power output	23 hp
CERTIFICATIONS	
Clutch rating	117.96 Nm
Power rating	1715 W
DIMENSIONS	
Article gross weight	345367 g
Article net weight	276238 g
Base machine, height	101.6 cm
Base machine, length	190.5 cm
Base machine, width (chute down)	152.4 cm
Base machine, width (chute up)	127 cm
Base machine, width	150 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Deck thickness	3.4 mm
Seat back height	High
Weight	269.89 kg
Wheel/rim size, front Diameter	5 in
Wheel/rim size, rear Diameter	8 in
ENGINE	
Cylinder displacement	726 cm³
Cylinders	2
Engine cooling	Air
Engine name	FR Series
Motor/engine manufacturer	Kawasaki
Motor/engine model	FR 691V
Fuel tank volume	13.25 l
Fuel tank volume	3.5 gal (US)
EQUIPMENT	
12V outlet	No
Air filter type	Auto-type Paper
All-Wheel Drive (AWD)	No
Anti-scalp wheels	3
Ball bearing wheels	No
Ball bearing front wheels	Yes
BioClip® kit	Available as accessory
Blade brake clutch (BBC)	Yes
Blade engagement	Electric clutch
Blade type	High-Lift blade
Blades	3 pcs
Collector	Available as accessory
Collector type	Fabric
Cup holder	Yes
Cutting deck type	ClearCut™ - Fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	Included
Detachable transmission	No
Drive method	Lever-operated
Drive system	Rear wheel drive

Technical Specifications	
Drive wheels	Rear
Electric start	Yes
Fan-cooled pumps	Yes
Foldable seat	No
Headlights	Yes
Hinged armrests	Standard
Hour meter type	Digital with pre-programmed service intervals
Hydraulic equipment lift	No
Nose roller	Yes
Parking brake, type	Mechanical
Seat manufacturer	Milsko
Seat spring	Yes
Seat suspension	No
Seat type	Comfort high back
Throttle control	Yes
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	4.163 l
Fuel tank location	Side (Single)
Fuel type, min	87 octane
Oil capacity	2.1 l
Oil filter	Yes
Oil type	10W30
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	1084 g
PE total	715 g
PET total	0 g
Plastic foil	520 g
Plastic rigid	200 g
Plastic total	720 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS total	0 g
Rims, material	Steel
Seat material	Vinyl
Spindle/mandrel type	Cast iron
PACKAGING	
Packaging height	876 mm
Packaging length	1981 mm
Packaging volume	2710 dm ³
Packaging width	1562 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	110 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	80 dB(A)