




Husqvarna Z242E

Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Husqvarna ZTR mowers offer cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance Clear Cut™ fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.



Rugged frame and casters

The robust frame and casters ensure durability and reduced chassis flex.



Maintenance-Free Transmission

Worry free performance with maintenance free, integrated zero-turn transmissions.

ClearCut™ fabricated cutting deck

ClearCut™ deck technology features deep deck design, air flow control baffles, high performance blades and top discharge for superior cutting performance whether discharging, bagging or mulching.



Convenient deck lift

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.



FEATURES

- ClearCut™ fabricated cutting deck
 - Maintenance-free hydraulic transmission
 - Rugged frame and casters ensure durability
 - Convenient deck lift
 - Removable foot plate
 - Anti-slip foot area
- Bumper
 - Dust protection
 - Automatic park brake system
 - Powerful two-cylinder Kawasaki engine
 - Rear engine guard
 - Ergonomic control panel

Technical Specifications	
BATTERY	
Battery capacity	18 Ah
Battery manufacturer	East Penn
Battery type	Lead-Acid
Battery voltage	12 V
CAPACITY	
Blade-tip speed	93.98 m/s
Power output	18 hp
DIMENSIONS	
Article gross weight	321597 g
Article net weight	252197 g
Base machine, height	101.6 cm
Base machine, length	190.5 cm
Base machine, width (chute down)	129.54 cm
Base machine, width (chute up)	110 cm
Base machine, width	122 cm
Cutting height steps	6
Deck thickness	3.5 mm
Gross weight	315.3 kg
Seat back height	High
Weight	250.38 kg
ENGINE	
Cylinder displacement	603 cm³
Cylinders	2
Engine cooling	Air
Engine name	FR Series
Motor/engine manufacturer	Kawasaki
Motor/engine model	FR600V
Fuel tank volume	13.25 l
Fuel tank volume	3.5 gal (US)
EQUIPMENT	
12V outlet	No
Air filter type	Auto-type Paper
All-Wheel Drive (AWD)	No
Anti-scalp wheels	1
BioClip® kit	Available as accessory
Blade brake clutch (BBC)	Yes
Blade engagement	Electric clutch
Blade type	High-Lift blade
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	ClearCut™ - Fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	Included
Drive method	Lever-operated
Drive system	Rear wheel drive
Drive wheels	Rear
Electric start	Yes
Headlights	No
Hinged armrests	Optional
Hour meter type	Digital with pre-programmed service intervals
Hydraulic equipment lift	No
Nose roller	Yes
Seat spring	Yes
Seat type	15" high back
Throttle control	Yes
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	4.012 l
Fuel tank location	Side (Single)
Oil capacity	2.1 l

Technical Specifications	
Oil cooler	No
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	1084 g
PE total	715 g
PET total	0 g
Plastic foil	520 g
Plastic rigid	200 g
Plastic total	720 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS total	0 g
Seat material	Vinyl
Spindle/mandrel type	Cast iron
PACKAGING	
Packaging, gross weight	69.16 kg
Packaging height	876 mm
Packaging length	1981 mm
Packaging volume	2710 dm ³
Packaging width	1562 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	110 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	80 dB(A)

ACCESSORIES



ZTR® ZERO TURN DOUBLE BIN
COLLECTION SYSTEM
587 41 24-01