


Husqvarna Z146

Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore.



Superior Quality Cut

Air Induction™ mowing technology lifts grass up straight for a higher-quality cut



Premium Integrated Transmission

Lasts longer with reduced maintenance thanks to zero-turn specific features



Easy to use and spring-assisted for reduced effort



Ultra-Durable Frame

Rugged frame and wheels ensure durability and long-lasting performance



FEATURES

- Easy to use and spring-assisted for reduced effort
- Lasts longer with reduced maintenance thanks to zero-turn specific features
- Air Induction™ mowing technology lifts grass up straight for a higher-quality cut
- Rugged frame and wheels ensure durability and long-lasting performance
- 46 in. cutting deck is reinforced with heavy flat-stock steel for added strength and durability
- Dust protection
- Brake automatically engages and disengages as steering levers are moved in and out
- Rear engine guard

BATTERY	
Battery capacity	18 Ah
lattery manufacturer	East Penn
lattery type	Lead-Acid
Battery voltage	12 V
CAPACITY	
Output shaft power	21.5 hp
DIMENSIONS	
urticle gross weight	297562 g
urticle net weight	233604 g
lase machine, height	101.6 cm
ase machine, length	190.5 cm
ase machine, width (chute down)	143.51 cm
ase machine, width (chute up)	122 cm
ase machine, width	111.13 cm
tutting height adjuster	Fender-mounted
utting height steps	6
eat back height	High
leight (complete product w/o side packed articles)	263 kg
NGINE	
Cylinder displacement	726 cm ³
Sylinders	2
ngine cooling	Air
ingine name	FR Series
uel tank volume	13.25
uel tank volume	3.5 gal (US)
fotor/engine manufacturer	Kawasaki
QUIPMENT	
ir filter type	Auto-type Paper
Anti-scalp wheels	3
SioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High-Lift blade
lades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped, Reinforced
Cutting methods	Collect/Mulch/Side discharge
leck lifting system	Manual, hand operated
leck Wash Port	Yes
rive method	Lever-operated
rive system	Rear wheel drive
rive wheels	Rear
lectric start	Yes
linged armrests	Optional
lose roller	No
Parking brake, type	Integrated
Seat type	15" high back
UBRICANTS	
ingine lubrication type	Full pressure with oil filter
uel consumption	0.0733 l/min
uel tank location	Side (Single)
Dil capacity	2.11
il filter	Yes
ower/fuel type	Gasoline
IATERIALS	
utting deck material	Steel
Master pack: Paper material	0 g
laster pack: Paper material Metal total	1200 g
Paper material total	0 g
IDPE (02) total	09
	0g
PET (O.1) total	
ET (01) total lastic foil total	450 g

Plastic total	1350 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS (06) total	0 g
Seat material	Vinyl
Spindle/mandrel type	Cast Aluminum
PACKAGING	
Packaging height	889 mm
Packaging length	1981 mm
Packaging volume	2727 dm ³
Packaging width	1549 mm
Quantity in Master pack	1