



HUSQVARNA R 216

Efficient Rider with 94cm Combi cutting deck, offering first-class BioClip® and rear ejection cutting. The articulated steering system and front-mounted cutting deck means intuitive operation, excellent mowing accessibility and great overview of your working area. Pedal-operated hydrostatic transmission, easy-access controls and automatic blade engagement, makes mowing a pleasure. Equipped with LED headlights and adjustable steering wheel with optional steering wheel knob.



Versatile usage

A wide range of cutting decks and attachments will make your front mower exceptionally versatile, all year round.



BioClip®

BioClip® (mulching) provides excellent cutting results on frequently cut areas. The grass is cut into fine pieces that quickly decompose and return to the lawn as natural fertiliser.

LED head lights

LED lights for improved visibility and enlarged lighted area in darker conditions.



Service position

Service position on the cutting deck facilitates cleaning and servicing.



FEATURES

- LED headlights for improved visibility and safer operation even in darker conditions.
- 595084001 mode for frequently cut areas
- Accessories for versatile year-round usage
- Service position for easy deck maintenance
- Turn key start
- Combi cutting deck
- Automatic blade engagement
- Pedal-operated hydrostatic transmission
- Pivoting rear axle for maximum traction
- Height adjustable steering wheel
- Easy-access storage compartment
- Easy-access cutting height lever
- Hour meter
- Bottle holder
- Min. clearance circle by articulated steering
- Comfortable driver's position
- Easy-access controls for user comfort
- Engine behind driver for better overview
- Equally sized wheels for a comfortable ride
- Front-mounted deck for optimum accessibility
- With the smart Husqvarna Connect app, you'll have easy access to tips, manuals and spare part recommendations. The app also provides additional information such as runtime and charging status as well as maintenance and service needs. **not yet available in all countries**

Technical Specifications	
BATTERY	
Battery capacity	24 Ah
Battery manufacturer	Global
Battery pack weight	7.2 kg
Battery type	Lead-Acid
Battery voltage	12 V
Quantity of batteries/battery pack	1 pcs
CAPACITY	
Power output	9.6 kW
DIMENSIONS	
Base machine, height	107 cm
Base machine, length	190 cm
Base machine, width	89 cm
Cutting height steps	10
Ground clearance	105 mm
Gross weight towed	110 kg
Tyre dimensions, front	165/60-8
Tyre dimensions, rear	165/60-8
Weight	197 kg
Wheelbase	88.7 cm
ENGINE	
Cylinder displacement	500 cm ³
Cylinders	1
Electric start	Yes
Engine cooling	Air
Engine lubrication type	Pressure
Engine name	Intek
Motor/engine manufacturer	Briggs & Stratton
Motor/engine model	INTEK 4155 EFM
Spark plug	Champion QC12YC, EMS Q
Fuel tank volume	12 l
Fuel tank volume	3.2 gal (US)
EQUIPMENT	
12V outlet	No
Air filter type	Cartridge
All-Wheel Drive (AWD)	No
Blade engagement	Automatic
Cup holder	Yes
Drive method	Pedal-operated
Drive system	Rear wheel drive
Foldable seat	Yes
Frame construction type	Box frame
Hour meter type	Digital
Seat manufacturer	SEAT
Seat suspension	Yes
Service position	Yes
Technical Platform	R 200-series
Wheelbase	88.7 cm
LUBRICANTS	
Engine lubrication type	Pressure
Fuel consumption	398 g/kWh
Fuel tank volume	12 l
Oil capacity	1.5 l

Technical Specifications

Oil filter	Yes
Oil type	SAE10W30
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Quantity in Master pack	1
EMISSION DATA EU	
Exhaust emissions (CO2 EU V)	794 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	100 dB(A)
Sound power level, measured	99 dB(A)
Sound pressure level at operators ear	85 dB(A)
VIBRATIONS	
Vibration level seat	0.7 m/s ²
Vibration level steering wheel	2.5 m/s ²