



HUSQVARNA 572XP

The 572 XP® has a better power-to-weight ratio than any other Husqvarna saw with similar displacement, and 12% higher cutting capacity than previous equivalent models. Excellent cooling and heavy-duty filtration mean great performance, while smart design and easy operation keep productivity high even with long guide bars.



[CONTACT A DEALER](#)

Article number: 966733140

TECHNICAL SPECIFICATIONS

Article Number	966733140
Displacement, cc	70.6
Power, kW	4.3
Sound Pressure level, dB(A)	107
Sound Power level (LWA), dB(A)	120
Vibrations, front/rear handle, m/s ²	5.0/4.1
Weight excl. bar and chain, kg	6.6
Chain pitch, inches	3/8
Standard fit up. Bar length, inches	20"
Rec. bar length, inches	15-28
Inertia-activated chain brake	•

TrioBrake	–
Air Injection	•
X-Torq	•
Low Vib	•
AutoTune	•
RevBoost	–
Decompression valve	•
SmartStart	•
Air purge	•
Starting reminder	–
Combined choke/ stop control	•
Magnesium crankcase	•
Forged three-piece crankshaft	•
Quick release on air filter/air filter cover	•/•
Visible fuel level	•
Flip-up Fuel/Oil Caps	•
Vibration-dampened carburettor	•
Adjustable oil pump	•
Side-mounted chain tensioner	•
Tool-less chain tensioner	–
Captive bar nuts	•
Integrated loop for rope	–

Notes:

SOUND AND VIBRATION LEVELS

* Equivalent sound pressure level, as per ISO 22868, is calculated as the time-weighted energy sum for the sound pressure levels at various operational states. Typical variation for equivalent sound pressure level is a standard deviation of 1 dB(A).

** Equivalent vibration level, as per ISO 22867, is calculated as the time-weighted energy sum for the vibration levels at various operational states. Report data for equivalent vibration level has a typical statistical dispersion (standard deviation) of 1 m / s².

Table key:

- = Standard
- (•) = Optional
- = Not applicable