

HUSQVARNA Z560X

The Husqvarna Z500 series zero turn mower represents the latest design focused on productivity, durability and cut quality. Providing extreme comfort, high ground speeds and superior traction adds up to exceptional mowing efficiency. Industrial strength throughout the entire design assures a long & durable service life in commercial mowing applications. Careful design consideration provides unprecedented ease in serviceability.



LED fuel gauge

The automotive style LED fuel gauge lets you know exactly how much fuel is remaining and warns you when you are too low.



AGM Battery

A smaller and more robust battery adopted from the transportation industry provides better reliability, improved longevity and more service space.



10" diameter commercial cast aluminium spindles with tapered roller bearings more effectively spread impact loads for extended durability.



Heavy duty fabricated cutting deck

A deep draw deck, heavy duty cutting blades and an efficient flow design allow for rapid cut speeds with a high quality finish.



FEATURES

- Cast aluminium spindles
- AGM Battery
- Automotive style LED fuel gauge
- Heavy duty fabricated cutting deck
- Automatic parking brake
- The discharge chute is built of heavy-duty rubber to withstand wear and tear while protecting nearby property.
- HydroGear ZT5400 Transmissions handles even the biggest jobs in landscaping
- Deck height adjustment
- Easily foldable ROPS protects the user
- Large fuel capacity
- Comfortable, user-focused controls put everything needed to operate the mower within easy reach.
- Premium suspension seat for increased comfort

Technical Specifications	
BATTERY	
Battery capacity	12 Ah
Battery pack weight	3.1 kg
Battery type	Lead-Acid
Battery voltage	12 V
Cells per battery	6
Quantity of batteries/battery pack	1 pcs
Weight of one battery	6.83 lbs
CAPACITY	0.03 lb3
	20.00
Blade-tip speed	93.98 m/s
Power output	31 hp
CERTIFICATIONS	
Clutch rating	338.95 Nm
DIMENSIONS	
Article gross weight	716676 g
Article net weight	599649 g
Base machine, height (ROPS down)	117 cm
Base machine, height (ROPS up)	185 cm
aase machine, height Base machine, height	117 cm
Base machine, length	206 cm
Base machine, width (chute down)	188 cm
Base machine, width (chute up)	161.9 cm
Base machine, width	136 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Manual
Cutting height steps	16
Deck thickness	4.76 mm
landle height adjustment	Yes
Seat back height	High
Veight	594 kg
Wheel/rim size, front Diameter	6.5 in
Wheel/rim size, rear Diameter	12 in
ENGINE	46-111
	000 3
Cylinder displacement	999 cm ³
Cylinders	2
ingine cooling	Air
ingine name	FX Series
Motor/engine manufacturer	Kawasaki
Motor/engine model	921V
uel tank volume	45.41
uel tank volume	12 gal (US)
QUIPMENT	
L2V outlet	No
ir filter type	Heavy-Duty Canister Style
ill-Wheel Drive (AWD)	No
	4
Inti-scalp wheels	
Ball bearing wheels	No
Ball bearing front wheels	Yes
SioClip® kit	Not available as accessory (NOT AVAILABLE)
lade brake clutch (BBC)	Yes
lade engagement	Electric clutch
lade type	High Performance
lades	3 pcs
ollector	Available as accessory
Cup holder	Yes
Cutting deck type	7-gauge fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, foot assisted
Deck Wash Port	No No
Deflector	Included
Detachable transmission	Yes
Drive method Drive system	Lever-operated Rear wheel drive

Technical Specifications	
Drive wheels	Rear
Electric start	Yes
Fan-cooled pumps	Yes
Foldable handlebar	No
Foldable seat	No
Front-End Protection	
	None
Handle type	Anti-vibration
Headlights	No
Hinged armrests	Standard
Hour meter type	Yes
Hydraulic equipment lift	No
Nose roller	No
Parking brake, type	Mechanical
Pivoting rear axle	No
Pneumatic drive	No
Reverse gearbox	No
Seat adjustment	Tool-less, while seated
·	
Seat manufacturer	Seats Inc
Seat spring Seat s	Yes
Seat suspension	Yes
Seat type	Premium, suspension
Side adjustable handle	Yes
Throttle control	Yes
Track, rear	54.63 in
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	6.7 l
·	
Fuel tank location	Side (Dual)
Oil capacity	1.91
Oil cooler	Yes
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	
PE total	0 g
	880 g
PET total	Og
PET total Plastic foil	0 g 525 g
PET total Plastic foil Plastic rigid	0 g 525 g 355 g
PET total Plastic foil Plastic rigid Plastic total	0 g 525 g 355 g 880 g
PET total Plastic foil Plastic rigid Plastic total	0 g 525 g 355 g
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck	0 g 525 g 355 g 880 g
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total	0 g 525 g 355 g 880 g Yes
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material	0 g 525 g 355 g 880 g Yes 0 g Steel
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels	0 g 525 g 355 g 880 g Yes 0 g Steel Included
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material	0 g 525 g 355 g 880 g Yes 0 g Steel Included Vinyl
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims. material Rubber wheels Seat material Spindle/mandrel type	0 g 525 g 355 g 880 g Yes 0 g Steel Included
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING	0 g 525 g 355 g 880 g Yes 0 g Steel Included Vinyl Cast iron
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims. material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging. gross weight	0 g 525 g 355 g 880 g Yes 0 g Steel Included Vinyl Cast iron
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height	0 g 525 g 355 g 880 g Yes 0 g Steel Included Vinyl Cast iron
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging length	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height Packaging length Packaging volume	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm 5086.91 dm³
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height Packaging length Packaging volume Packaging volume Packaging width	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm 5086.91 dm³ 1740 mm
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height Packaging length Packaging volume Packaging width Quantity in Master pack	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm 5086.91 dm³
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height Packaging length Packaging volume Packaging width Quantity in Master pack SOUND AND NOISE	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm 5086.91 dm³ 1740 mm 1
PET total Plastic foil Plastic rigid Plastic total Powder-coated cutting deck PS/EPS/HIPS total Rims, material Rubber wheels Seat material Spindle/mandrel type PACKAGING Packaging, gross weight Packaging height Packaging length Packaging volume Packaging width Quantity in Master pack	0 g 525 g 3355 g 880 g Yes 0 g Steel Included Vinyl Cast iron 117 kg 1346 mm 2172 mm 5086.91 dm³ 1740 mm