

HUSQVARNA RC 320Ts AWD with 103cm Combi Deck

The RC 320Ts AWD Rider offers durable effectiveness, versatility and ease of use though innovative design. Its unique, non-clogging collection system feeds clippings straight from the front-mounted cutting deck to the 300 I bag. Automatic compaction increases run time between emptying, so you get more done. Articulated powered steering allows easy tight turns for superior manoeuvrability. All Wheel Drive means superior power and traction in all conditions. Cutting deck servicing and cleaning is tool-free, thanks to the unique 90° service position. Unbeaten area coverage and huge collection capacity make this a truly worthwhile investment for larger gardens. Price is complete with Combi Deck 103 (103cm).



All-Wheel-Drive (AWD)

All-Wheel-Drive (AWD) ensures traction on uneven, wet and slippery areas and slopes. AWD automatically adjusts the traction on all wheels depending on situation and ground condition.

Turn key start Easy to get operating under any weather conditions. No choking needed, just turn the key and go.



Empty collector from seat The integrated collector is easily emptied from the driver's seat

ACTech

Non-clog collection. Compacting grass in collector, meaning bigger area coverage. The efficient collection leaves a clean lawn as a result.



FEATURES

- All-Wheel Drive secure traction on all areas
- Non-clog collection and compacting of grass in collector.
- Turn key start
- Empty collector from seat
- Switch from collecting to non-collecting with a push on the button
- Articulated steering for excellent manoeuvrability
- Power steering makes more enjoyable drive
- Pedal-operated hydrostatic transmission
- Tilting hood makes maintenance quick and easy
- Easy-access controls for user comfort
- Front-mounted deck for optimum accessibility
- Service position for easy deck maintenance
- Equally sized wheels for a comfortable ride

- Automatic blade engagement
- Pivoting rear axle for maximum traction
- Comfortable driver's position
- Engine behind driver for better overview
- Floating cutting deck for reduced risk of scalping
- Hour meter with service minder
- Gives over 50% larger lighted area compared to traditional incandescent lights.
- 12V socket outlet for electric equipment
- Easy-access cutting height lever
- External fuel cap for easy refueling
- Pivoting support wheels on the cutting deck
- Easy fuel level check by transparent fuel tank
- Attachment frame for maximum versatility

Partner Softwart Barber praviourburter BNZ Barber praviourburter L2A Barber praviourburter L2A Barber praviourburter L2A Barber praviourburter L2A Dament of barber praviourburter L2A Barber praviourburter L2A Barber praviourburter L2A Dament of barber praviourburter L2A Barber praven L2A	Technical Specifications	
Battery park weight BMZ Battery park weight 11 kg Battery park weight 12 kW Dattery for batteriek/hattery park 1 pcs CANACITY P Priver cubal 12 kW DMENSIONS 472000 g Arritle ret weight 472000 g Arritle ret weight 22 kW DMENSIONS 22 kW Arritle ret weight 22 kW Base machine, keight 2000 g Base machine, keight 200 g Base machine, keight 100 cm Canter to weight 20 cm Canter to weight 20 cm Cant	BATTERY	
Elling'ypack seight 11 kg Battary type L/bon Battary type 128 V Dentry oblighter (Selar Selar	Battery capacity	5.5 Ah
Battery type 11 kg Battery type 12 kV Battery type 12 kW Battery type 12 kW Diversion type 12 kW Diversion type 472000 g Artice gross weight 390000 g Base machene keight 390000 g Base machene keight 286 g en Base machene keight 3001 Cutting height stess 7 Gound clearance 90 rmm Type dimensions front 166.5 -8 Weight 328 kg Weight ded cutting sequement 66.0 em ³ Optimet displacement 66.0 em ³ Optimet displacement 66.0 em ³ Optinde displacement 720.0	Battery manufacturer	BMZ
Battery type Lion Dattery type Lion Quenty for blankine/haltery pack I.P.S. CAPACITY I.P.S. Former output. 12.6 kW DimensionS 472000 g. Article miss weight 472000 g. Article miss weight 2000 g. Base machine. height 12.6 k.M. Base machine. height 20.8 g.cm. Base machine. height 3001 Collector vulume 3001 Collector vulume 3001 Collector vulume 90 rmm Type dimensions. ford 16:65-80 Type dimensions. ford 16:65-81 Type dimensions. ford 16:60 Collector		1.1 kg
Ishtery visitage 12.8 V Constry of Statery Sector 12.6 NW Power output 12.6 NW Power output 12.6 NW Dimess sector 390000 g Base machen, lenght 390000 g Base machen, lenght 390000 g Base machen, lenght 20.8 g om Base machen, lenght 3001 Cattery other and the sector 3001 Up and the sector 3001 Yee dimensions, foot 166.5-8 Yee dimensions foot 328 kg Weight (act catter output other and the sector 328 kg Weight (act catter output other and the sector 2 Cyfrider diglocenneri 560 cm ³ Cyfrider diglocenneri 700 Sector path catter 110 Cyfrider diglo		
Quartic of batteries/battery pack 1 pcs Power output 12.6 kW Power output 12.6 kW DIMENSIONS 472000 g Article gross weight 472000 g Article gross weight 128.4 cm Base machine, height 128.4 cm Base machine, height 208.9 cm Base machine, height 3001 Collidors valume 303 cm Collidors valume 3001 Collidors valume 3001 Collidors valume 3001 Ype dimensions. foot 1665.5 -8 Ype dimensions. fear 308 kg Weight (sed cuting equipment) 328 kg Weight (sed cuting equipment) 32		12.8 V
CAPACITY 126 W Power output 126 W Dimbensions 472000 g Article gross weight 472000 g Article gross weight 472000 g Base machine. height 309000 g Base machine. height 208 9 cn Base machine. keight 300 1 Base machine. keight 300 1 Chitter previsions. front 103 cm Chitter previsions. front 1665 5-8 Tyre dimensions. front 328 kg Weight (kcit cuting equipment) 328 kg Weight (kcit cuting equipment) 328 kg Weight (kcit cuting equipment) 328 kg Cyfinder displacement 656.0 cm ³ Cyfinder displacement 720 Cyfinder displacement		1 pcs
Difference Project Article gross weight 472000 g Article gross weight 390000 g Base machine. height 1284 cm Base machine. length 2081 g cm Base machine. length 103 cm Collector volume 3001 Cond clearance 90 mm Tyse dimensions. form 16x65-8 Weight 328 kg Weight (act culting equipment) 47 Cylinder displacement 6660 cm³ Cylinder displacement 6660 cm³		'
Article gross weight 472000 g Artice net weight 390000 g Base machine height 1284 cm Base machine height 2089 cm Base machine keight 2089 cm Base machine keight 3001 Callector volume 3001 Callector volume 3001 Callector volume 3001 Callector volume 90 mm Tyse dimensions. front 16x65-8 Tyse dimensions. front 16x65-8 Viged fill (xcl. cutting equipment) 328 kg Weight (xcl. cutting equipment) 4500 cm ² Cylinder (kp	Power output	12.6 kW
Article rise weight390000 gBase machine, height128.4 cmBase machine, height208.9 cmBase machine, height103 cmBase machine, witht103 cmCollector volume300 lCatter beight steps7Ground clearance90 mmTyre dimensions. Fornt156.6 5-8Weight328 kgWeight fuel cutting euipment)328 kgWeight fuel cutting euipment)456 Cm ³ Cylindrid eligbacement656.0 cm ³ Cylindrid eligbacement656.0 cm ³ Cylindrid eligbacement656.0 cm ³ Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cylindrid eligbacement72.0Cy	DIMENSIONS	
Article retweight390000 gBase machine height128.4 cmBase machine height208.9 cmBase machine with103 cmCollector volume3001Cutting height steps7Gound clearance90 mmTyre dimersions: front166.5-8Weight328 logWeight (sucl cutting equipment)328 logWeight (sucl cutting equipment)47Cylinder displacement655.0 cm ³ Cylinder displacement72.0Cylinder displacem	Article gross weight	472000 g
IBase machine, height 128.4 cm Base machine, length 208.9 cm Base machine, width 103 cm Collector volume 3001 Collector volume 90 mm Tyre dimensions, front 16s6.5 -8 Tyre dimensions, front 16s6.5 -8 Tyre dimensions, front 328 kg Weight 328 kg Weight (secl.cuting exipment) 328 kg Cylinders 2 Exities att 120 Exities att Yes Engine exoling 4m Engine exoling 720 Spark plug Charapion XC92VC Forgen exame 121 Engine exoling 121 <		
Base machine, length 208 9 cm Base machine, width 103 cm Catter, volume 3001 Cutting height steps 7 Ground clearance 90 mm Tyre dimensions, front 1665 5-8 Weight 328 kg Weight (act cutting equipment) 328 kg Weight (act cutting equipment) 328 kg Weight (act cutting equipment) 328 kg Vinetabase 50.3 cm ENCINE Cylinder displacement Cylinder displacement 656.0 cm ³ Cylinder displacement 656.0 cm ³ Cylinder displacement 720 Engine acoling Ar Engine acoling Ar Engine acoling Ar Engine acoling Ar Engine model 7220 Spark hulp Champion K/S29/C Elaf ank volume 121 Fuel tank volume 121 Fuel tank volume 21/200 Spark hulp Yees Eduphoter Yees Cuttin		
Base machine width 103 cm Collector volume 3001 Culting height steps 7 Gound Clearance 90 nm Tyre dimensions front 16x6.5–8 Tyre dimensions front 16x6.5–8 Weight 328 kg Weight (ect culting equipment) 328 kg Weight (ect culting equipment) 328 kg Wheelbase 90.3 cm ENNINE 2 Cylinder stipplacement 656.0 cm ³ Cylinders 2 Extrix start Yes Engine lubrication type Full pressure Engine lubrication type Full pressure Engine lubrication type Full pressure Engine lubrication type Engine lubrication type Engine lubrication type Champion XC92YC Engine lubrication type Statton Motor engine model 7220 Spark plug Champion XC92YC Fuel tark volume 121 Tartist volume Cartinge with pre filter 12/V outlet Yes	· · · · · · · · · · · · · · · · · · ·	
Collector volume3001Cutting height steps7Cutting height steps90 mmTyre dimensions front16x65-8Weight328 kgWeight (excl cutting equipment)328 kgWight (excl cutting equipment)328 kgWight (excl cutting equipment)328 kgWight (excl cutting equipment)4000Cylinder steps2Endurence steps656.0 cm³Cylinder steps2Endurence Setes4000Motor/engine manufacturerBridging S StrattonMotor/engine model7220Spark plugCharmignox KS29CVFuel tark volume121Fuel tark volume121Fuel tark volume317 gal (US)EQUIPMENT12212V cutletYesAir Hiter typeCarringe with pre filterAir Hiter typeCarringe with pre filterAir Hiter typeCarringe with pre filterAir Hiter typeStart typeCutting digit adjustmentLever, while satedDrive methodPedal-operatedDrive method<	· · · ·	
Cutting height steps7Ground clearance90 mmTyre dimensions, front16x6.5 - 8Tyre dimensions, front16x6.5 - 8Tyre dimensions, rear16x6.5 - 8Weight328 kgWeight (sed: cuting equipment)328 kgWheebbase90.3 cmENINECCylinder displacement6550 Cm ³ Cylinder displacement6550 Cm ³ Cylinders2Efectric startYesEngine Lubrication typeFull pressureEngine Lubrication typeFull pressureEngine Lubrication typeFull pressureEngine Lubrication typeFull pressureEngine Nationation typeChampion XC92YCFuel tark volume121Fuel tark volume121Fuel tark volume121Cuting equipmentYes12V outetYesAr Itter typeAutomaticAr Itter typeAutomaticCuting the typeYesEduration typeStartuonEduration typeYesEduration typeYesIzV outetYesAr Itter typeAutomaticCuting height adjustmentLever while seatedDurbuscYesCuting height adjustmentLever while seatedDrive queblesYesFrame construction typeSquare tubeFrame construction typeSquare tubeSeat supersionYesFrame construction typeSpaleSeat supersionYes		
Gound clearance 90 mm Tyre dimensions rear 16x65-8 Weight 328 kg Weight (act, cuting equipment) 328 kg Wheebase 90.3 cm ENKINE		
Tyre dimensions front16:65-8Tyre dimensions, rear16:65-8Weight328 kgWeight (sell cutting equipment)328 kgWheeblase90.3 cmENINE00.3 cmCylinder displacement656.0 cm³Cylinder displacement656.0 cm³Cylinders2Entris statYesEngine lubrication typeFull pressureEngine lubrication typeFull pressureEngine lubrication typeFull pressureEngine lubrication typeFull pressureEngine lubrication type720Spark plugChampion NC92YCFuel tark volume121Fuel tark volume121Fuel tark volume31.7 gal (US)EQUIPMENTYes12V cutletYesAir filter typeCatrindge with pre filterAir filter typeYesCutting deck typeSampedCutting deck typeSampedCutting deck typeSampedCutting deck typeSampedCutting deck typeSampedCutting height adjustmentPeda-operatedDrive systemAveled driveFidate scalaperationYesCutting height adjustmentSampedSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionSampedSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspe		
Tyre dimensions, rear 16x6 5-8 Weight 328 kg Weight (act cuting equipment) 328 kg Wheelbase 90.3 cm ENCINE 90.3 cm ENCINE 656.0 cm ³ Cylinder displacement 656.0 cm ³ Cylinders 2 Engine cooling Air Engine cooling Air Engine name Endurance Series Motor/engine manufacturer Briggs & Straton Motor/engine manufacturer Briggs & Straton Motor/engine manufacturer 121 Fuel tank volume 121 Engine name Champion XC92YC Fuel tank volume 121 Evaluation Yes Edutance Series Motor/engine model 12V outiet Yes Champion XC92YC Series Bidde engagement Catritidge with pre filter All-Yheel Dive (AWD) Yes Bidde engagement Ves Cuting begit Adjustment Lever, while seated Dive system Keidabe seat Dive system All-Wheel dive		
Weight 328 kg Weight 656 0 cm³ Cylinders 2 Electric start 656 0 cm³ Engine tubrication type Full pressure Engine tubrication type Endurance Series Motor/engine manufacturer Briggs & Straton Motor/engine model 7220 Spark plug Champion XC92YC Fuel tank volume 121 Fuel tank volume 121 Fuel tank volume 317 gal (US) EQUPMENT Yes Librate Drive (AWD) Yes Bidae engagement Automatic Cutting deck type Catridge with pre filter Air filter type Automatic Cutting deck type Stamped Cutting deck type Square tube	· · · · · · · · · · · · · · · · · · ·	
Weight (excl. cutting equipment) 328 kg Wheelbase 90.3 cm ENRINE 656.0 cm ³ Cylinder displacement 656.0 cm ³ Cylinders 2 Electric start Yees Engine cooling Air Engine cooling Air Engine name Endurance Series Motor/engine manufacturer Briggs & Stratton Motor/engine model 7220 Spark plug Champion XC92VC Fuel tank volume 121 Fuel tank volume 317 gal (US) EQUIPMENT 2 12V outlet Yees Air Hiter type Automatic Automatic Yees Blade engagement Automatic Cutting dekt type Stamped Cutting dekt type Stamped Cutting dekt type Stamped Cutting dekt type Stamped Equipment Yees Cutting dekt type Stamped Cutting dekt type Stamped Cutting dekt type		
Wheelbase 90.3 cm ENGINE 0 Cylinder displacement 656.0 cn ³ Cylinder displacement 2 Engric start Yes Engrice coling Air Engrice coling Full pressure Engrine name Endurance Series Motor/engrine manulacturer Briggs & Stratton Motor/engrine manulacturer Briggs & Stratton Motor/engrine manulacturer 21 Spark plug Champion XC92YC Fuel tank volume 121 Fuel tank volume 3.17 gal (US) EQUIPMENT Yes L2V outlet Yes Air filter type Chartinge with pre filter All-Wheel Drive (AWD) Yes Bade engagement Automatic Cutting deck type Stargned Cutting deck type <td< td=""><td></td><td></td></td<>		
ENGINECylinder displacement656.0 cm3Cylinders2Electric startYesEngine coolingAirEngine coolingFull presureEngine tubrication typeEndurance SeriesEngine nameBriggs & StrattonMotor/engine manufacturerBriggs & StrattonMotor/engine manufacturer7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume31.7 gal (US)EQUIPMENTYes12V outetYesAir filter typeAutomaticCuting dex typeStarpedCuting dex typeStarpedDrive methodYesFoldale seatYesFoldale seatYesFormetrer typeSugare tubeHour meter typeSugare tubeFour methodStarpedSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionYes		
Cylinder displacement656.0 cm³Cylinders2Electric startYesEngine coolingAirEngine lubrication typeFull pressureEngine nameEndurance SeriesMotor/engine manufacturerBriggs & StrattonMotor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUMENTYes12V outletYesAlr filter typeCatrindge with pre filterAlr filter typeYesCutting deck typeStampedCutting height adjustmentYesDrive methodPeda-operatedDrive methodPeda-operatedDrive methodYesCutting height adjustmentYesDrive methodPeda-operatedDrive methodYesFurthereStampedCutting deck typeAll-wheel driveFurthereYesStatuentYesDrive methodPeda-operatedDrive methodSquare tubeHour meter typeDigitalSeat suspensionStartSeat suspensionYesSeat suspensionYes <td< td=""><td></td><td>50.5 Cm</td></td<>		50.5 Cm
Öylinders 2 Electric start Yes Engine cooling Air Engine lubrication type Full pressure Engine name Endurance Series Motor/engine manufacturer Briggs & Stratton Motor/engine model 7220 Spark plug Champion XC92YC Fuel tank volume 121 Fuel tank volume 3.17 gal (US) EQUIPMENT Yes 12V outlet Yes Air filter type Cartridge with pre filter All-Wheel Drive (AWD) Yes Blade engagement Yes Cutting height adjustment Yes Drive extend Peda-operated Drive system All-wheel drive Fordenent Yes Farme construction type Square tube Hour meter type Digital Seat suspension Yes Seat suspension Yes Farme construction type Seat suspension Seat suspension Yes		050.0
Électric start Yes Engine ecoling Air Engine cooling Full pressure Engine name Endurance Series Motor/engine manufacturer Briggs & Straton Motor/engine model 7220 Spark plug Champion XC92VC Fuel tank volume 121 Fuel tank volume 121 Fuel tank volume 317 gal (US) EQUPMENT 2 12V outlet Yes Air filter type Cartridge with pre filter All-Wheel Drive (AWD) Yes Blade engagement Automatic Cutting deck type Stamped Cutting deck type Stamped Drive method Pedai-operated Drive system Al-wheel drive Foldale seat Yes Forme construction type Square tube Hour meter type Digital Seat rungateur Seat rungateur Fuels subgension Yes		
Engine coolingAirEngine hubrication typeFull pressureEngine nameEndurance SeriesMotor/engine manufacturerBriggs & StrattonMotor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUIPMENT1212V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCutting deck typeStampedCutting deck typeStampedCutting deck typeAll-Wheel driveDrive systemAll-Wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeSquare tubeHour meter typeSquare tubeHour meter typeSquare tubeHour meter typeSquare tubeFarme construction typeYesSeat suspensionYesService positionYes		
Engine lubrication typeFull pressureEngine nameEndurance SeriesMotor/engine manufacturerBriggs & StrattonMotor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUIPMENT12112V outletYesAll-Wheel Drive (AWD)YesBlade engagementAutomaticCutting deck typeStampedCutting deck typeStampedCutting deck typeStampedDrive methodPedal-operatedDrive methodYesFoldable seatYesFrame construction typeYesFoldable seatYesFoldable seatYesFoldable seatYesFoldable seatYesFoldable seatYesSeat suppensionSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesService positionYesSeat suppensionYesSeat suppensionYesSeat suppensionYesYesService positionYes		
Engine nameEndurance SeriesMotor/engine manufacturerBriggs & StrattonMotor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume317 gal (US)EQUIPMENTYes12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCutting height adjustmentLever. while seatedDrive systemAll-wheel drivePoldels seatYesFrame construction typeSquare tubeHour meter typeSquare tubeFor anufacturerSearsingSeat suppensionYesFarame construction typeSeatSeat suppensionYesService positionYesService positionYes		
Motor/engine manufacturerBriggs & StrattonMotor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUIPMENTYes12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodYesFidable seatYesFoldable seatYesFrame construction typeSquare tubeHour meter typeSquare tubeHour meter typeDigitalSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionYesSeat suspensionYesService positionYesService positionYes		
Motor/engine model7220Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUIPMENT12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCup holderYesCutting height adjustmentLever, while seatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeSquare tubeHour meter typeDigitalSeat suspensionYesService positionYes	~	
Spark plugChampion XC92YCFuel tank volume121Fuel tank volume3.17 gal (US)EQUIPMENT12V outlet12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFlodable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat supensionYesService positionYes		
Fuel tank volume 121 Fuel tank volume 317 gal (US) EQUIPMENT	v	
Fuel tank volume3.17 gal (US)EQUIPMENTYes12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat supensionYesService positionYes		
EQUIPMENT12V outletYes12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes		
12V outletYesAir filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat suspensionYesService positionYes		3.17 gal (US)
Air filter typeCartridge with pre filterAll-Wheel Drive (AWD)YesBlade engagementAutomaticCup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes	•	
All-Wheel Drive (AWD) Yes Blade engagement Automatic Cup holder Yes Cutting deck type Stamped Cutting height adjustment Lever, while seated Drive method Pedal-operated Drive system All-wheel drive Foldable seat Yes Frame construction type Square tube Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes		
Blade engagementAutomaticCup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes	//	
Cup holderYesCutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes		
Cutting deck typeStampedCutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes		
Cutting height adjustmentLever, while seatedDrive methodPedal-operatedDrive systemAll-wheel driveFoldable seatYesFrame construction typeSquare tubeHour meter typeDigitalSeat manufacturerSEATSeat suspensionYesService positionYes		
Drive method Pedal-operated Drive system All-wheel drive Foldable seat Yes Frame construction type Square tube Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes		
Drive system All-wheel drive Foldable seat Yes Frame construction type Square tube Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes		
Foldable seat Yes Frame construction type Square tube Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes		
Frame construction type Square tube Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes	,	
Hour meter type Digital Seat manufacturer SEAT Seat suspension Yes Service position Yes		
Seat manufacturer SEAT Seat suspension Yes Service position Yes	Frame construction type	
Seat suspension Yes Service position Yes		
Service position Yes		
Technical Platform R 300 Collection	Technical Platform	R 300 Collection

Technical Specifications	
Wheelbase	90.3 cm
LUBRICANTS	
Engine lubrication type	Full pressure
Fuel consumption	360 g/kWh
Fuel tank volume	121
Oil capacity	1.91
Oil cooler	Yes
Oil filter	Yes
Oil type	10W-30
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	Og
Metal total	0 g
Paper + Cardboard total	Og
PE total	0 g
PET total	Og
Plastic foil	0 g
Plastic rigid	Og
Plastic total	0 g
PS/EPS/HIPS total	Og
PACKAGING	
Packaging, gross weight	82 kg
Quantity in Master pack	1
EMISSION DATA EU	
Exhaust emissions (CO2 EU V)	830 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	100.0 dB(A)
Sound power level, measured	99.0 dB(A)
Sound pressure level at operators ear	85.0 dB(A)
VIBRATIONS	
Vibration level seat	0.7 m/s ²
Vibration level steering wheel	2.6 m/s ²