



## HUSQVARNA TS 354

Heavy duty garden tractor with unbeaten capabilities in its class. Versatile ClearCut™ cutting deck and powerful, reliable engine mean fast mowing anytime, anywhere – with a perfect result every time. Commercial grade ground-engaging transmission with dash operated differential lock works with large, wide rear tyres to enable tough usage without overheating, plus great traction and less damage to the lawn. Improved quality, comfort and ergonomics for an optimal driving and ownership experience. Driven by a powerful and robust, Kawasaki, twin cylinder engine.



### Hydrostatic transmission with locking differential

The commercial graded, pedal-operated hydrostatic transmission offers a smooth, variable forward and reverse speed and allows tough usage without risk of overheating. Electric locking rear differential increases traction while cutting on slopes or wet grass



### Electric engagement of cutting blade/s

Easy engagement of cutting blade/s; simply pull the switch on the control panel.

### ClearCut™ fabricated cutting deck

The new fabricated design features welded 10 gauge steel construction with additional welded reinforcement strips for maximum durability



### Pedal-operated hydrostatic transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.



## FEATURES

- ClearCut™ fabricated cutting deck
- Electric engagement of cutting blade/s
- Hydrostatic transmission with locking differential
- Pedal-operated hydrostatic transmission
- High quality tyres for longer tyre life and improved traction.
- Cast front axle for superior stability
- Cruise control for comfortable operation
- Durable, cast iron spindle housings
- Easy-access fuel cap
- High Back Seat
- Large, wide rear tyres for improved traction
- Gives over 50% larger lighted area compared to traditional incandescent lights.
- Robust and durable steel chassis
- Hour meter with service minder
- Brushguard for protection of the hood
- Deck Wash Port
- Ergonomic steering wheel
- Easy-access cutting height adjustment
- Fuel level window

### Technical Specifications

<b>BATTERY</b>	
Battery voltage	12 V
<b>CAPACITY</b>	
Power output	17.9 kW
Turning radius, min	18 in
<b>DIMENSIONS</b>	
Article gross weight	387368 g
Article net weight	311164 g
Base machine, height	127 cm
Base machine, length	180 cm
Base machine, width (chute down)	170 cm
Base machine, width (chute up)	142 cm
Base machine, width	170 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	7
Cutting width	137 cm
Seat back height	Extra high 21"
Tyre dimensions, front	16X6.5-8
Tyre dimensions, rear	23X10.5-12
Tyre size, rear Diameter	23 in
Tyre size, rear Width	10.5 in
Weight	305 kg
Wheel/rim size, front Diameter	8 in
Wheel/rim size, rear Diameter	12 in
Wheelbase	122 cm
<b>ENGINE</b>	
Cylinders	2
Cylinder displacement	726 cm <sup>3</sup>
Engine cooling	Air
Engine name	FR Series
Generator	15 A
Motor/engine manufacturer	Kawasaki
Motor/engine model	FR 730V
Transmission manufacturer	Tuff Torq
Transmission model	K66 ELD
Transmission type	Commercial Grade Hydrostat, Electric Locking Differential
Fuel tank volume	15.1 l
Fuel tank volume	4 gal (US)
<b>EQUIPMENT</b>	
Air filter type	Auto-type Paper
Anti-scalp wheels	4
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High-Lift blade
Blades	3 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	ClearCut™ - Fabricated
Cutting Methods (filter)	Collecting, Mulching, Side discharge
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	Included
Drive method	Pedal-operated
Front-End Protection	Brush Guard Style Bumper
Generator	15 A

Technical Specifications	
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Mulching kit	Available as accessory
Powder-coated cutting deck	Yes
Seat type	Premium High back 21" with armrest
<b>LUBRICANTS</b>	
Engine lubrication type	Full pressure with oil filter
Fuel tank location	Rear
Oil capacity	2.1 l
Oil filter	Yes
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	3286 g
PE total	407 g
PET total	0 g
Plastic foil	45 g
Plastic rigid	377 g
Plastic total	422 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	110 dB(A)
Sound power level, measured	110 dB(A)
<b>PACKAGING</b>	
Packaging height	1270 mm
Packaging length	1905 mm
Packaging volume	3626.6 dm <sup>3</sup>
Packaging width	1499 mm
Quantity in Master pack	1

## ACCESSORIES



TOW BEHIND AERATOR 36"  
540 00 00-73

576 21 75-01



TOW BEHIND AERATOR 48"  
968 99 92-36



SPREADER - LARGE  
967 02 72-01



SPREADER - SMALL  
589 40 93-01



LARGE RIDE-ON COVER  
505 63 08-82



LOADING RAMPS  
505 69 90-43



BATTERY CHARGER BC 0.8 12V /  
0.8  
579 45 01-02



BATTERY STATUS INDICATOR  
579 45 21-01