




HUSQVARNA T525

Our lightest tree-care chainsaw gives you performance when it matters, whether for part-time or full-time professional use. The Husqvarna top-handled T525 has a low-weight design and includes a powerful, low-emission X-Torq® petrol engine for professional performance, ease of use and safety for all your pruning and trimming jobs.




Retained bar nut

The retaining function prevents losing the bar nut.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



Belt eyelet

Makes it quick and easy to connect the saw to the climbing harness.



Chain tensioning from the side

Allows quick and convenient chain tensioning.



FEATURES

- Quick connection to the climbing harness
- Auto return stop switch for easy starting
- The retaining function prevents losing the bar nut.
- Quick and easy chain adjustment
- Easy to maintain with tool-less air filter cover
- Air purge for easier cold starting
- The flip-up tank cap is easy to open.
- Smart Start® for easy starting

PXM_TechnicalSpecifications	
CAPACITY	
Chain speed at 133% of maximum engine power speed	24.1 m/s
Chain speed at max power	18.1 m/s
Clutch engagement speed (±120)	4200 rpm
Idling speed	2900 rpm
Ignition module air gap	0.4 mm
Maximum power speed	13500 rpm
Power output	1.1 kW
Racing speed lower limit	12500 rpm
Torque, max.	1.28 Nm
Torque, max. at rpm	6000 rpm
CERTIFICATIONS	
Approved according to CE	Yes
Eurotested	Yes
DIMENSIONS	
Bar length (inch)	12"
Product size height	21.2 cm
Product size length	26.5 cm
Product size width	21.8 cm
Recommended bar length, max	30 cm
Recommended bar length, min	20 cm
Size	12"
Weight (excl. cutting equipment)	2.7 kg
ENGINE	
Cylinder bore	35 mm
Cylinder displacement	27 cm ³
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Ignition module air gap	0.4 mm
Spark plug	NGK CMR6A
EQUIPMENT	
Bar mount	Small
Bar mount type	Small
Chain type	H37
Chainsaw sub-group	Tree-care saws
Gauge	1.3 mm
Handle type	Standard
Pitch	3/8"
Source system	PAID
Sprocket type	Spur
LUBRICANTS	
Fuel consumption	408 g/kWh
Fuel tank volume	0.19 l
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Oil pump type	Adjustable flow
Oil tank volume	0.17 l
Power source	Petrol
Power/fuel type	Gasoline
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	111 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	98 dB(A)
VIBRATIONS	
Daily Vibration (Aeqv)	5.2 m/s ²
Daily Vibration Exposure (A8)	2.8 m/s ²
Daily Vibration Time (Time factor)	2.4 h
Equivalent vibration level (ahv, eq) front handle	4.9 m/s ²
Equivalent vibration level (ahv, eq) rear handle	5.2 m/s ²
EMISSION DATA EU	
Exhaust emissions (CO2 EU V)	850 g/kWh
PACKAGING	
Packaging height	260 mm
Packaging length	480 mm
Packaging volume	0.044 m ³
Packaging volume	43.68 dm ³
Packaging width	350 mm
Quantity in Master pack	1
Unit	Piece/Each

