



HUSQVARNA TS 142TXD

Ideal for homeowners who need a durable and comfortable tractor with high manoeuvrability. It is a powerful tractor with side ejection for demanding lawn care. The new deep-cushioned, stitched seat and oversized steering wheel with rubber inlay offer superior comfort, while the locking differential transmission gives superior traction in slippery conditions and slopes. Driven by a powerful Kawasaki V-Twin engine. Pedal-operated hydrostatic transmission and cast front axle means easy, trouble-free operation. Collector and BioClip® kit are available as accessories.



Pedal-operated Automatic transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.



Steel hood

Hood in solid steel construction, guarantees reduced paint fade compared to plastic.

Automatic locking differential

The standard automatic locking differential senses wheel slip and locks the rear wheels for increased traction.



LED lights with high intensity

High intensity and large lighted area with focused pattern. For safer operation in darker conditions.



FEATURES

- Automatic locking differential
- Solid steel hood
- Speed and direction are managed by pedals.
- LED lights with high intensity
- Deluxe comfort seat for an improved ride quality
- Deluxe steering wheel for better ergonomics
- Brushguard for protection of the hood
- Rubber isolator for solid feel and reduced vibration
- Electric blade engagement
- Air Induction; excellent cutting performance
- Reinforced Cutting Deck
- Cast front axle for superior stability
- Hour meter with service minder
- Deck Wash Port
- Cup holder for refreshments while mowing

Technical Specifications	
BATTERY	
Battery voltage	12 V
CAPACITY	
Power output	16.0 kW
Turning radius, min	16 in
DIMENSIONS	
Article gross weight	286670 g
Article net weight	222714 g
Base machine, height	127 cm
Base machine, length	180 cm
Base machine, width (chute down)	124 cm
Base machine, width (chute up)	110 cm
Base machine, width	124 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Cutting width	107 cm
Seat back height	High 15"
Tyre dimensions, front	15X6-6
Tyre dimensions, rear	20X10-8
Weight	220 kg
Wheelbase	122 cm
ENGINE	
Cylinders	2
Cylinder displacement	726 cm ³
Engine cooling	Air
Engine name	FR Series
Generator	15 A
Motor/engine manufacturer	Kawasaki
Transmission manufacturer	Tuff Torq
Transmission model	K46LD
Transmission type	Hydrostatic with Automatic Differential Lock
Fuel tank volume	11.4 l
Fuel tank volume	3 gal (US)
EQUIPMENT	
Air filter type	Auto-type Paper
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High Performance
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped, Reinforced
Cutting methods	Collect/Mulch/Side discharge
Deck Wash Port	Yes
Drive method	Pedal-operated
Front-End Protection	Brush Guard Style Bumper
Generator	15 A
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Powder-coated cutting deck	Yes
Seat type	Comfort high back
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel tank location	Rear
Oil capacity	1.9 l
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel

Technical Specifications

Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	2755 g
PE total	25 g
PET total	0 g
Plastic foil	35 g
Plastic rigid	0 g
Plastic total	35 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
PACKAGING	
Packaging height	1270 mm
Packaging length	1905 mm
Packaging volume	3072 dm ³
Packaging width	1270 mm
Quantity in Master pack	1