



HUSQVARNA TS 142T

Husqvarna TS 142T is a compact side discharge tractor with smart, user-friendly design, developed for use in small to mid-size gardens. Equipped with pedal-operated, hydrostatic transmission, 15" deluxe seat and ergonomic steering wheel.



Deluxe steering wheel

An oversized and extra thick steering wheel for less steering effort. Soft touch inner surface guarantees reduced effort and better ergonomics



Steel hood

Hood in solid steel construction, guarantees reduced paint fade compared to plastic.

Pedal-operated Automatic transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.



Hour meter with service minder

Indicates when it's time to service your mower.



FEATURES

- Speed and direction are managed by pedals.
- Solid steel hood
- Deluxe steering wheel for better ergonomics
- Hour meter with service minder
- Bumper for protecting the front
- Air Induction; excellent cutting performance
- Electric blade engagement
- Deck Wash Port
- Cup holder for refreshments while mowing
- Reinforced Cutting Deck
- Cast front axle for superior stability

Technical Specifications	
BATTERY	
Battery voltage	12 V
CAPACITY	
Net power at preset rpm	3600 rpm
Power output	19 kW
Turning radius, min	16 in
DIMENSIONS	
Article gross weight	277599 g
Article net weight	213642 g
Base machine, height	127 cm
Base machine, length	178 cm
Base machine, width (chute down)	124 cm
Base machine, width (chute up)	110 cm
Base machine, width	124 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Cutting width	107 cm
Seat back height	High 15"
Tyre dimensions, front	15X6-6
Tyre dimensions, rear	20X10-8
Weight	214 kg
Wheelbase	122 cm
ENGINE	
Cylinders	2
Cylinder displacement	764 cm ³
Engine cooling	Air
Engine name	Husqvarna Series
Generator	15 A
Motor/engine manufacturer	Husqvarna
Transmission manufacturer	Tuff Torq
Transmission model	K46
Transmission type	Hydrostatic
Fuel tank volume	5,7 l
Fuel tank volume	3 gal (US)
EQUIPMENT	
Air filter type	Auto-type Paper
Anti-scalp wheels	2
BioClip® Kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High Performance
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped, Reinforced
Cutting methods	Collect/Mulch/Side discharge
Deck Wash Port	Yes
Drive method	Pedal-operated
Front-End Protection	Tube Bumper
Generator	15 A
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Powder-coated cutting deck	Yes
Seat type	High back 15" (armrest as accessory)
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel tank location	Rear
Oil capacity	1.9 l
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	2303 g
PE total	25 g

Technical Specifications

PET total	0 g
Plastic foil	35 g
Plastic rigid	0 g
Plastic total	35 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
PACKAGING	
Packaging height	1270 mm
Packaging length	1905 mm
Packaging volume	3072 dm ³
Packaging width	1270 mm
Quantity in Master pack	1