



## HUSQVARNA TS 242TXD

Husqvarna TS 242TXD is a powerful and comfortable side discharge tractor with sturdy ClearCut™ deck and smart, user-friendly design, developed for use in medium- to large-sized gardens. Dual Pedal-operated hydrostatic transmission and cast front axle means easy, trouble-free operation and the locking differential transmission gives superior traction in slippery conditions and slopes. Equipped with 15" deluxe seat, soft rim steering wheel, LED lights and turn key start. Collector and BioClip® kit are available as accessories.



### Deluxe comfort seat

Deluxe comfort seat features premium vinyl, stitched design and extra thick cushions for improved comfort and superb ride quality.



### Deluxe steering wheel

An oversized and extra thick steering wheel for less steering effort. Soft touch inner surface guarantees reduced effort and better ergonomics.

### ClearCut™ fabricated cutting deck

The new fabricated design features welded 10 gauge steel construction with additional welded reinforcement strips for maximum durability.



### Rubber isolator

Rubber isolator for solid feel and reduced vibration.



## FEATURES

- ClearCut™ fabricated cutting deck
- Deluxe steering wheel for better ergonomics
- Deluxe comfort seat for an improved ride quality
- Rubber isolator for solid feel and reduced vibration
- Powerful two-cylinder Kawasaki engine
- Solid steel hood
- Brushguard for protection of the hood
- Cast front axle for superior stability
- Cruise control for comfortable operation
- LED lights with high intensity
- Durable, cast iron spindle housings
- Deluxe Gauges
- Electric blade engagement
- Deck Wash Port
- Dual pedal drive for better drive control
- Automatic locking differential

Technical Specifications	
<b>BATTERY</b>	
Battery voltage	12 V
<b>CAPACITY</b>	
Power output	16.0 kW
Turning radius, min	16 in
<b>DIMENSIONS</b>	
Article gross weight	321597 g
Article net weight	257640 g
Base machine, height	127 cm
Base machine, length	178 cm
Base machine, width (chute down)	124 cm
Base machine, width (chute up)	110 cm
Base machine, width	124 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Cutting width	107 cm
Seat back height	High 15"
Tyre dimensions, front	15X6-6
Tyre dimensions, rear	20X10-8
Weight	257 kg
Wheelbase	122 cm
<b>ENGINE</b>	
Cylinders	2
Cylinder displacement	726 cm <sup>3</sup>
Engine cooling	Air
Engine name	FR Series
Generator	15 A
Motor/engine manufacturer	Kawasaki
Transmission manufacturer	Tuff Torq
Transmission model	K46LD
Transmission type	Hydrostatic with Automatic Differential Lock
Fuel tank volume	15.1 l
Fuel tank volume	4 gal (US)
<b>EQUIPMENT</b>	
Air filter type	Auto-type Paper
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High Performance
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	ClearCut™ - Fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck Wash Port	Yes
Drive method	Dual pedal-operation
Front-End Protection	Brush Guard Style Bumper
Generator	15 A
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Powder-coated cutting deck	Yes
Seat type	Comfort high back
<b>LUBRICANTS</b>	
Engine lubrication type	Full pressure with oil filter
Fuel tank location	Rear
Oil capacity	1.9 l
Oil filter	Yes
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Cutting deck material	Steel

**Technical Specifications**

Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	2755 g
PE total	25 g
PET total	0 g
Plastic foil	35 g
Plastic rigid	0 g
Plastic total	35 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
<b>PACKAGING</b>	
Packaging height	1270 mm
Packaging length	1905 mm
Packaging width	1270 mm
Quantity in Master pack	1